

9164G



M **USO SINISTRO** **HSS-E**

Orig. Vökel - Art. 334

GAMBO RINFORZATO

USO SINISTRO

FILETTATURA METRICA ISO-Conforme DIN 13 (DIN 371) Metrico Grosso M-Tolleranza ISO2/6H.

HSS-E. Tipo universale. Imbocco corto. Fori ciechi e passanti.

Ø.....	mm	3	4	5	6	8	10
Passo.....	mm	0,5	0,7	0,8	1	1,25	1,5
Lungh. totale.....	mm	56	63	70	80	90	100
Lungh. filetto.....	mm	11	13	16	19	22	24
Ø gambo.....	mm	3,5	4,5	6	6	8	10
Quadro gambo.....	mm	2,7	3,4	4,9	4,9	6,2	8
9164G	Cad.	27,10	27,10	27,10	27,60	27,60	36,70

9170G



M **HSS-E**

Orig. Vökel - Art. 375

GAMBO RINFORZATO

USO DESTRO

FILETTATURA METRICA ISO-Conforme DIN 13 (DIN 371) Metrico Grosso M-Tolleranza ISO2/6H.

HSS-E. Imbocco corretto. Per metalli fino a R 900 N/mm², acciai legati e non legati. Fori passanti.

Ø.....	mm	1	1,1	1,2	1,4	1,6	1,7	1,8	2	2,5	3	4	5	6	8	10
Passo.....	mm	0,25	0,25	0,25	0,3	0,35	0,35	0,35	0,4	0,45	0,5	0,7	0,8	1	1,25	1,5
Lungh. totale.....	mm	40	40	40	40	40	40	40	45	50	56	63	70	80	90	100
Lungh. filetto.....	mm	5	5	5	7	8	8	8	8	9	11	13	16	19	22	24
Ø gambo.....	mm	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,8	2,8	3,5	4,5	6	6	8	10
Quadro gambo.....	mm	2,1	2,1	2,1	2,1	2,1	2,1	2,1	2,1	2,1	2,7	3,4	4,9	4,9	6,2	8
9170G	Cad.	34,10	34,10	34,10	34,10	34,10	34,10	34,10	18,60	18,60	9,76	9,90	11,50	11,60	14,90	20,10

9172G



M **HSS-E**

Orig. Vökel - Art. 320

Descrizione di riferimento vedi Art. 9170G

HSS-E. Imbocco corretto. Per metalli fino a R 900 N/mm², acciai legati e non legati. Fori passanti.

Tipo lungo ed extra-lungo.

Tipo.....		3	4	4A	4B	5	5A	5B	6	6A	6B
Ø.....	mm	3	4	4	4	5	5	5	6	6	6
Passo.....	mm	0,5	0,7	0,7	0,7	0,8	0,8	0,8	1	1	1
Lungh. totale.....	mm	100	100	120	150	100	120	150	100	120	150
Lungh. filetto.....	mm	11	13	13	13	16	16	16	19	19	19
Ø gambo.....	mm	3,5	4,5	4,5	4,5	6	6	6	6	6	6
Quadro gambo.....	mm	2,7	3,4	3,4	3,4	4,9	4,9	4,9	4,9	4,9	4,9
9172G	Cad.	21,70	21,70	23,30	24,80	23,30	25,30	27,10	23,30	25,30	27,10
Tipo.....		8	8A	8B	10	10A	10B	12	12A	12B	
Ø.....	mm	8	8	8	10	10	10	12	12	12	
Passo.....	mm	1,25	1,25	1,25	1,5	1,5	1,5	1,75	1,75	1,75	
Lungh. totale.....	mm	100	120	150	100	120	150	100	120	150	
Lungh. filetto.....	mm	22	22	22	24	24	24	29	29	29	
Ø gambo.....	mm	8	8	8	10	10	10	12	12	12	
Quadro gambo.....	mm	6,2	6,2	6,2	8	8	8	9	9	9	
9172G	Cad.	27,90	29,40	33,10	29,10	33,20	40,30	32,80	38,70	47,20	

9174G



M **TIN** **HSS-E**

Orig. Vökel - Art. 315 TIN

Descrizione di riferimento vedi Art. 9170G

HSS-E-TIN. Imbocco corretto. Per metalli fino a R 900 N/mm², acciai legati e non legati. Fori passanti.

Con rivestimento TIN.

Ø.....	mm	3	4	5	6	8	10
Passo.....	mm	0,5	0,7	0,8	1	1,25	1,5
Lungh. totale.....	mm	56	63	70	80	90	100
Lungh. filetto.....	mm	11	13	16	19	22	24
Ø gambo.....	mm	3,5	4,5	6	6	8	10
Quadro gambo.....	mm	2,7	3,4	4,9	4,9	6,2	8
9174G	Cad.	15,20	15,40	16,90	17,80	22,60	30,10

Tutte le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.

Prezzi in EURO - IVA esclusa