


TABELLE DIMENSIONI ATTACCHI
Tabella N. 10

Mandrino		Cono DIN 238/1		Cono JACOBS - UNI 5887/66	
Tipo	Ø mm	D	L	D	L
B 10 e J 1	0-6,5	10,094	18	9,754	20,2
B 12 e J 2G	0-8	12,065	22	13,940	22,5
B 16 e J 2	0-10	15,733	29	14,199	25,7
B 16 e J 6	1-13	15,733	29	17,170	30,4
B 18 e J 6	3-16	17,780	37	17,170	30,4
B 22	5-20	21,793	45,5	—	—
B 24	6-26	23,825	55,5	—	—


Tabella N. 11

DIMENSIONE ATTACCHI CONO MORSE											
Gr.	Conicità	A	B (max)	C (max)	D (max)	E (max)	F	G	H	J	K
0	19.212:1	9.045	56.5	59.5	10.5	6	4	1	3	3.9	1° 29' 27"
1	20.047:1	12.065	62	65.5	13.5	8.7	5	1.2	3.5	5.2	1° 25' 43"
2	20.020:1	17.780	75	80	16	13.5	6	1.6	5	6.3	1° 25' 50"
3	19.922:1	23.825	94	99	20	18.5	7	2	5	7.9	1° 26' 16"
4	19.254:1	31.267	117.5	124	24	24.5	8	2.5	6.5	11.9	1° 29' 15"
5	19.002:1	44.399	149.5	156	29	35.7	10	3	6.5	15.9	1° 30' 26"
6	19.180:1	63.348	210	218	40	51	13	4	8	19	1° 29' 36"
7	19.231:1	83.058	285.75	294.1	34.9	-	-	19.05	-	19	1° 29' 22"

**TABELLA
ATTACCHI
CONO MORSE**
